

PRODUCT: Low VOC Rubberized Undercoating

PART NUMBER: 101348 17.75 oz 12units/case

DESCRIPTION: Evercoat's premium Rubberized Undercoating is a VOC-compliant product that provides maximum protection against stone chips, and abrasion. It offers a slightly smooth texture that can be painted over in 2 hours without bleed through. Rubberized Undercoating is ideally suited for rocker panels, splash pan, wheel wells, trunks, lower body panels and under bodies.

FEATURES & ADVANTAGES:

- VOC Compliant
- Best protection against stone chipping and abrasion
- Excellent adhesion.
- Can be painted over
- Textured finish

SUBSTRATES:

- Bare Metal
- Painted surfaces

CLEANING:

- Surface must be clean, dry and free of dirt, oil, grease, wax and rust
- Wash all substrates to be coated with a mild detergent and hot water, rinse well and wipe dry with a clean cloth
- Solvent clean all areas to be coated with a quality wax and grease remover and wipe dry with a clean, dry cloth
- Mask area if desired

APPLICATION:

- Shake can vigorously, for at least three minutes. Shake aerosol until mixing ball breaks free.
- If application is in a tight area or if overspray is a concern use an extension tube
- Hold can so nozzle is 12 to 16 inches from surface Apply 2 or 3 even coats for full coverage Apply by moving steadily and evenly
- Allow each coat to flash off for 5 minutes between coats

TECHNICAL SPECIFICATIONS:

| | |
|----------------|---|
| Appearance | Black |
| VOC | Refer to Section 9 of the Safety Data Sheet |
| Physical State | Aerosol |

SAFETY & HANDLING:

Read all directions and warnings prior to using Evercoat products. Safety Data Sheets can be found online at www.evercoat.com.



a division of Illinois Tool Works Inc. | 6600 Cornell Road | Cincinnati, OH 45242 | (513) 489-7600
Made and Printed in the U.S. | ©2015 Evercoat

evercoat.com

300-310-101348-TDS

2.2015