

# MATERIAL SAFETY DATA SHEET

# 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product name: FUSOR 129 CONTROLLED FLOW SEAM SEALER PT A

Product Use/Class: **EPOXY ADHESIVE, PART 1 OF 2** 

LORD Corporation 111 LORD Drive Cary, NC 27511-7923

Telephone: 814 868-3180

Non-Transportation Emergency: 814 763-2345 Chemtrec 24 Hr Transportation Emergency No.

800 424-9300 (Outside Continental U.S. 703 527-3887)

**EFFECTIVE DATE: 08/25/2014** 

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Chemical Name</u>	CAS Number	Weight % Less Than	ACGIH TLV- TWA	ACGIH TLV- STEL	OSHA PEL- TWA	OSHA PEL- CEILING	<u>Skin</u>
Epoxy resin	PROPRIETARY	85.0 %	N.E.	N.E.	N.E.	N.E.	N.A.

N.A. - Not Applicable, N.E. - Not Established, S - Skin Designation

### 3. HAZARDS IDENTIFICATION

\*\*\* **EMERGENCY OVERVIEW** \*\*\*: White Paste, with Epoxy odor. May cause skin and eye irritation. May cause allergic skin reaction. May cause respiratory tract irritation.

EFFECTS OF OVEREXPOSURE - EYE CONTACT: May cause eye irritation.

**EFFECTS OF OVEREXPOSURE - SKIN CONTACT:** May cause allergic skin reaction. May cause skin irritation.

**EFFECTS OF OVEREXPOSURE - INHALATION:** May cause respiratory tract irritation.

**EFFECTS OF OVEREXPOSURE - INGESTION:** Harmful if swallowed. Ingestion is not an expected route of entry in industrial or commercial uses.

**EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS:** Prolonged or repeated contact may result in dermatitis.

PRIMARY ROUTE(S) OF ENTRY: Skin Contact, Inhalation, Ingestion, Eye Contact

## 4. FIRST AID MEASURES

**FIRST AID - EYE CONTACT:** Flush eyes immediately with large amount of water for at least 15 minutes holding eyelids open while flushing. Get prompt medical attention.

**FIRST AID - SKIN CONTACT:** Flush contaminated skin with large amounts of water while removing contaminated clothing. Wash affected skin areas with soap and water. Get medical attention if symptoms occur.

**FIRST AID - INHALATION:** Move person to fresh air. Restore and support continued breathing. If breathing is difficult, give oxygen. Get immediate medical attention.

**FIRST AID - INGESTION:** If swallowed, do not induce vomiting. Call a physician or poison control center immediately for further instructions. Never give anything by mouth if victim is rapidly losing consciousness, unconscious or convulsing.

300000007726

Product: FUSOR 129 CONTROLLED FLOW SEAM SEALER PT A, Effective Date:

08/25/2014

#### 5. FIRE-FIGHTING MEASURES

**FLASH POINT:** ≥ 201 °F, 93 °C **LOWER EXPLOSIVE LIMIT (%):** Not Applicable Setaflash Closed Cup **UPPER EXPLOSIVE LIMIT (%):** Not Applicable

**AUTOIGNITION TEMPERATURE:** N.D.

**EXTINGUISHING MEDIA:** Carbon Dioxide, Dry Chemical, Foam, Water Fog

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Keep containers tightly closed. Closed containers may rupture when exposed to extreme heat. Use water spray to keep fire exposed containers cool. During a fire, irritating and/or toxic gases and particulate may be generated by thermal decomposition or combustion.

**SPECIAL FIREFIGHTING PROCEDURES:** Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA). If water is used, fog nozzles are preferable.

# 6. ACCIDENTAL RELEASE MEASURES

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Avoid breathing vapors. Notify appropriate authorities if necessary. Avoid contact. Use appropriate respiratory protection for large spills or spills in confined area. Keep non-essential personnel away from spill area. Scoop spilled material into an appropriate container for proper disposal. (If necessary, use inert absorbent material to aid in containing the spill).

### 7. HANDLING AND STORAGE

**HANDLING:** Keep closure tight and container upright to prevent leakage. Avoid skin and eye contact. Wash thoroughly after handling. Do not handle until all safety precautions have been read and understood. Empty containers should not be re-used. Use with adequate ventilation.

STORAGE: Store only in well-ventilated areas. Keep container closed when not in use.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**ENGINEERING CONTROLS:** Sufficient ventilation in pattern and volume should be provided in order to maintain air contaminant levels below recommended exposure limits.

**RESPIRATORY PROTECTION:** Use a NIOSH approved air-purifying organic vapor respirator if occupational limits are exceeded. For emergency situations, confined space use, or other conditions where exposure limits may be greatly exceeded, use an approved air-supplied respirator. Observe OSHA regulations (29CFR 1910.134) for respirator use.

**SKIN PROTECTION:** Use neoprene, nitrile, or rubber gloves to prevent skin contact.

**EYE PROTECTION:** Use safety eyewear including safety glasses with side shields and chemical goggles where splashing may occur.

**OTHER PROTECTIVE EQUIPMENT:** Use disposable or impervious clothing if work clothing contamination is likely. Remove and wash contaminated clothing before reuse.

**HYGIENIC PRACTICES:** Wash hands before eating, smoking, or using toilet facility. Food or beverages should not be consumed anywhere this product is handled or stored. Wash thoroughly after handling.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

ODOR: Epoxy BOILING RANGE: N.A. APPEARANCE: White VAPOR PRESSURE: N.D.

Page: 2

Product: FUSOR 129 CONTROLLED FLOW SEAM SEALER PT A, Effective Date:

08/25/2014

PHYSICAL STATE: Paste VAPOR DENSITY: Heavier than Air **ODOR THRESHOLD:** N.D. **EVAPORATION RATE:** Slower than n-butyl-

acetate

**SOLUBILITY IN H2O:** Insoluble **DENSITY, LB/GL:** 7.8000 lb/gal pH: N.A. **VOLATILE BY WEIGHT:** 0.13 % FREEZE POINT: N.D. **VOLATILE BY VOLUME:** 0.11 %

COEFFICIENT OF WATER/OIL N.D.

**DISTRIBUTION:** 

(See section 16 for abbreviation legend)

## 10. STABILITY AND REACTIVITY

**CONDITIONS TO AVOID:** High temperatures.

INCOMPATIBILITY: Amines, acids, water, hydroxyl, or active hydrogen compounds.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide, aldehydes

HAZARDOUS POLYMERIZATION: Hazardous polymerization will not occur under normal conditions.

**STABILITY:** Product is stable under normal storage conditions.

## 11. TOXICOLOGICAL INFORMATION

PRODUCT LD50 No Data (ORAL) No Data (DERMAL)

PRODUCT LC50 No Data

### 12. ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: No Information

### 13. DISPOSAL CONSIDERATIONS

**DISPOSAL METHOD:** Disposal should be done in accordance with Federal (40CFR Part 261), state and local environmental control regulations. If waste is determined to be hazardous, use licensed hazardous waste transporter and disposal facility.

#### 14. TRANSPORT INFORMATION

This product is NOT REGULATED for non-bulk US DOT Road, IATA Cargo or IMDG shipments. For the most accurate shipping information, refer to your transportation/compliance department regarding changes in package size, mode of shipment or other regulatory descriptors.

### 15. REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS: AS FOLLOWS -

This product is considered hazardous as defined by 29 CFR 1910.1200 (OSHA HazCom Standard.)

#### **SARA SECTION 313**

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372.:

Page: 3

Product: FUSOR 129 CONTROLLED FLOW SEAM SEALER PT A, Effective Date:

08/25/2014

**NONE** 

#### TOXIC SUBSTANCES CONTROL ACT:

#### **INVENTORY STATUS**

The chemical substances in this product are on the TSCA Section 8 Inventory.

#### **EXPORT NOTIFICATION**

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

**NONE** 

### 16. OTHER INFORMATION

HMIS RATINGS - HEALTH: 2 FLAMMABILITY: 1 PHYSICAL HAZARD: 0

\* - Indicates a chronic hazard; see Section 3

#### **VOLATILE ORGANIC COMPOUNDS**

Calculated: 0 lb/gal, 0 g/l

**Revision:** Section 1

LEGEND: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

## **DISCLAIMER**

The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state and local laws and regulations.

Page: 4