

PRODUCT HIGHLIGHTS

4373

Rubberized Undercoat

DESCRIPTION:

Rubberized Undercoat is designed for use on new panel and fender replacements, section repairs, weld joints and rust holes as a sound deadener and rust preventative. Seals out dust fumes, heat and cold. For best results use at room temperature.

PRODUCTS:

4373 Rubberized Undercoat, 20 oz.aerosol (591 ml), 6/case



SURFACE PREP:

Clean with Aqua SCAT (TDS225), Speedi SCAT (TDS223) or SCAT (TDS222).



MIX RATIO:

Ready to spray.

*See next page for more detailed product application. See website for this document in other languages.
Vea la página siguiente para un uso más detallado del producto. Vea el Web site para este documento en español.
Voir la prochaine page pour une application plus détaillée de produit. Voir le site Web pour ce document en français.*

PRODUCT DATA

4373

Rubberized Undercoat

SUITABLE SUBSTRATES:

Painted or primed steel and aluminum wheel wells and frame rails.

SURFACE PREPARATION:

Clean with Aqua SCAT 2 (TDS225), Speedi SCAT (TDS223) or SCAT (TDS222).

APPLICATION:

1. Shake well. Clean surface using Aqua SCAT 2 (TDS225), Speedi SCAT (TDS223) or SCAT (TDS222).
2. Holding can 8- 10 inches from surface, apply 2- 3 light even coats. Short, even strokes will produce best results.
3. Remove overspray with Acry Solvent (TDS316).
4. When finished, invert can and spray until valve is free of material to prevent clogging.



IMPORTANT: On cars equipped with catalytic converters, exhaust components operate at temperatures exceeding 1000°F (520°C). Therefore, avoid application of undercoating and/ or rustproofing materials within 12" of the exhaust system.

TECHNICAL DATA:

APPEARANCE: Black

SHELF LIFE: 1 year unopened

REGULATORY:

Category: Undercoat 4373	Individual Component
VOC Content	<40%

ADVANTAGES:

- Fast drying
- 50 State & Canadian Compliant
- Economical
- Convenient aerosol requires no equipment cleanup
- Excellent coverage
- Excellent adhesion

COMPETITION:

3M 08881
Wurth 892071/72
Marhyde 4211
Dominion SS 24004
Montana SA210
Kent 50195

See website (www.tat-co.com) for this document in other languages.

Vea el Web site (www.tat-co.com) para este documento en español.

Voir le site Web (www.tat-co.com) pour ce document en français.

TRANSTAR AUTOBODY TECHNOLOGIES • 2040 HEISERMAN DRIVE, BRIGHTON, MI 48114 • (800) 824-2843

FAX (800) 477-7923 • EMAIL: info@tat-co.com