

OEM Bed Liner

Truck Bed & Underbody Coating

- Waterproof & Stain Resistant
- Easy Soap & Water Cleanup
- Prevents Chips & Scratches
- Permanently Flexible & Impact Resistant
- Professional Use

Protect and preserve surfaces exposed to impact and abrasion

POR-15® OEM Bed Liner is formulated to provide professional results and performance in a DIY system. POR-15® OEM Bed Liner is a water-based, rubberized coating ideal for protecting truck beds, and all other metal, aluminum, fiberglass, and wood surfaces that are exposed to impact and scuff related environments. Formulated with POR-15® rust preventive technologies, POR-15® OEM Bed Liner offers superior adhesion, impact resistance, and flexibility, as well as an attractive, texturized semi-gloss black finish that provides the ultimate in truck bed protection. POR-15® OEM Bed Liner is UV stable and will resist damage typically caused by UV exposure. POR-15® OEM Bed Liner is a lowodor product that can be cleaned with soap and water and does not have a limiting pot life. Any unused product can be resealed in its container and used later for touch-up or on other projects. For the ultimate in protection apply over POR-15[®] Rust Preventive Coating.



	PRODUCT	SIZE	CODE
-	OEM Bed Liner - Black	Qt.	49704
	OEM Bed Liner - Black	Gal.	49701

Features and Uses:

- Waterborne product
- Available in Quarts, Gallons, 5-Gallon Pails or Drums
- Cures rock hard
- Environmentally safe
- Easy clean-up
- Brush or roll
- Low VOC'S
- NO Isocyanates!!!
- Metal truck beds and running boards

- Rocker panels
- Wood and Metal
- Trailers
- Boat docks
- Fiberglass
- Tractor beds
- Aluminum
- Tool boxes
- · Work van floors
- · and other surfaces



Product Information

OEM Bed Liner

Truck Bed & Underbody Coating



Product Descripition

POR-15® OEM Bed Liner is formulated to provide professional results and performance in a DIY system. POR-15® OEM Bed Liner is a water-based, rubberized coating ideal for protecting truck beds, and all other metal, aluminum, fiberglass, and wood surfaces that are exposed to impact and scuff related environments. Formulated with POR-15® rust preventive technologies, POR-15® OEM Bed Liner offers superior adhesion, impact resistance, and flexibility, as well as an attractive, texturized gloss black finish that provides the ultimate in truck bed protection. POR-15® OEM Bed Liner is UV stable and will resist damage typically caused by exposure to UV. POR-15® OEM Bed Liner is a low-odor product that can be cleaned with soap and water and does not have a limiting pot life. Any unused product can be resealed in its container and used later for touch-up or on other projects. For the ultimate in protection apply over POR-15® Rust Preventive Coating.

Application Information

RECOMMENDED USES: Metal truck beds, rocker panels, wood, trailers, metal, boat docks, fiberglass, tractor beds, aluminum, tool boxes, running boards, work van floors.

Surface Preparation: Proper surface preparation is essential to achieve a high quality finish. Read the MSDS sheet and wear proper protection, which may include gloves, eye protection, and/or other protective devices. Previously Finished or Primed Surfaces: Using POR-15® Cleaner Degreaser ensures that the surface is clean, dry, and free from oil, grease, dirt, salts, and any other contaminants. All blistered and loose paint must be removed. All bare areas must be primed with POR-15® Rust Preventive Coating before a full coat is applied. Glossy surfaces should be roughened before recoating. Bare Steel: Using POR-15® Cleaner Degreaser clean all surfaces to ensure they are free of loose rust, mill scale and contaminants such as oil, grease, dirt, and salts. You must use POR-15® Metal Prep if you are painting on new steel, galvanized metal, aluminum, or any smooth metal surface.

Application Information: REMEMBER TO STIR THIS PRODUCT BEFORE AND DURING USE. A gallon of POR-15® OEM Bed Liner will cover approximately 100-120 square feet. This is enough coating to properly apply the recommended 2-coats to all standard-sized 6 foot truck beds. Apply when air, surface and product temperatures are above 50°F(10°C) and surface temperature is at least 5°F (3°C) above the dew point*. Avoid exterior application late in the day when dew and condensation are likely to form or if rain is expected. *Air and surface temperatures must remain above 50°F (10°C) for the next 24 hours. PROTECT FROM FREEZING. Once applied POR-15® OEM Bed Liner will be ready for light-duty use in 24 hours and regular use in 48 hours. Application Equipment: Brush Use a high quality

nylon brush. Roller Use all-purpose short nap shed resistant phenolic core roller. Clean Up Instructions: Clean hands and all tools using soap and water before POR-15® OEM Bed Liner has dried. Make sure the container lid is securely sealed back on to container. Unused POR-15® OEM Bed Liner can be used at any time.

Safety Information

FIRST AID: In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention immediately; for skin, wash thoroughly with soap and water. If you experience difficulty breathing, leave area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. If swallowed, do not induce vomiting. Get medical attention immediately.

HEALTH HAZARD INFORMATION: Vapor harmful. May affect the brain or nervous system causing dizziness, headache or nausea. Can Contains Glycol Ether DPM which can be absorbed through skin and cause damage to blood or cause birth defects. May cause skin, eye, nose and throat irritation. Harmful if swallowed.

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

USE ONLY WITH ADEQUATE VENTILATION. Do not breathe vapor or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor / mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use.

Do not get in eyes, on skin or clothing. Wash thoroughly after handling. If spilled, contain spilled material and remove with inert absorbant. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

⚠ WARNING: This product can expose you to chemicals including Carbon black and N-methyl-2-pyrrolidone, which are known to the State of California to cause cancer and/or birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

PROFESSIONAL USE. KEEP OUT OF REACH OF CHILDREN.

Refer to Material Safety Data Sheet available upon request for further safety and handling information.