

UP720 BARCOAT Quick Drying Isolator

Description

BARCOAT is a quick drying yellow oxide isolator. It is designed to prevent lifting and bleeding of existing paint film sensitive to solvent attack when overcoated with cellulose or paint containing strong solvents.

Health & Safety Statement

FOR PROFESSIONAL USE ONLY. Read full instructions before use. IMPORTANT: This product contains hazardous materials and therefore appropriate personal protective equipment should always be used. Please refer to the label and consult the material safety data sheet for full handling instructions and personal protection information. These are available via your local stockist or via the U-POL website at <u>WWW.U-POL.com</u>. U-POL disclaim any liability where the user does not wear the recommended personal protective equipment.

Surface preparation and instructions for use

Thoroughly clean and de-wax the old paint surface with a spirit wipe or suitable solvent. Wet sand with 400 grit abrasive, re-clean and dry thoroughly. For metal use 180 grit abrasive.

Application

Stir well and strain before use. Only one light even coat is necessary. Additional coats are not recommended - **BARCOAT** will not adhere to itself. Use a gravity feed HVLP gun with a 1.4 mm fluid tip. Check first that the air line is free of moisture.

Do not use silicone or flow additives or allow the paint film to become wet after application.

Thinners

BARCOAT is supplied ready for use, no thinners are required. Use alcohol based gun wash to clean equipment after use.

Build and pressure

One light even coat of **BARCOAT** will give a build of approximately 1 mil. A pressure of 40-50 psi is required at the gun.

Drying time

Approximately 1 hour at normal shop temperatures. Drying time is dependent on film thickness, humidity and temperature.

Over-painting

BARCOAT needs to be primered or sealed prior to topcoating. **BARCOAT** <u>cannot</u> be sanded before application of further coats of paint.

Product code

UP0720 - 1L can.

U-POL US, Inc., 630 Selvaggio Dr, Suite 300, Nazareth, PA 18064 Tel: (800) 340 7824; Fax: (800) 787 5150 Email: sales-us@u-pol.com Website: www.u-pol.com