



DRIVING SURFACE PERFECTION™

TECHNICAL DATA SHEET

# GUIDE#7

DRY GUIDE COAT AEROSOL



## DESCRIPTION

Dry powder guide coat used to highlight and identify surface imperfections when sanding fillers, primers or uneven surfaces

- Does not clog or block abrasives
- Suitable for dry or wet sanding
- Dries instantly
- Convenient aerosol application mean no waste, less mess, and no clean-up

## APPLICATION GUIDE



### Mixing

Shake the aerosol can for at least 2 minutes before use.



### Application

- Spray directly onto the cured body filler or primer.
- Allow to dry for a few seconds.
- Sand to required finish. Remaining low spots will show as black.

## STORAGE & VOC INFORMATION



### Shelf Life

2 years subject to proper storage conditions.

Aerosol cans should be stored for two hours at room temperature before use. For long term storage, keep in a dry well ventilated area and away from direct sunlight and frost. To maximize the lifespan of your aerosol, always invert the can and spray upside down for a few seconds after each use to clear the nozzle. If the nozzle becomes blocked, remove it from the can and soak it in gentle thinners.

Recommended Storage Temperature 41°F - 77°F

Recommended Application Temperature 68°F



### VOC Information

Order Code	Format	Color	MIR
UP0873	450ml Aerosol	Black	PAP 2.5

### IMPORTANT: FOR PROFESSIONAL USE ONLY. Read full instructions before use.

This product contains hazardous materials and therefore appropriate personal protective equipment should always be used. Please refer to the label and consult the safety data sheet for full handling instructions and personal protection information. U-POL disclaims any liability where the user does not wear the recommended personal protective equipment. The above data is for information only and may change without prior notice. It is the Buyers responsibility to ensure the suitability of the products for their own use and check the information is up to date. The recommendation of use of our products and application in our technical data sheets are based on our knowledge and experience. These data sheets are available via your local distributor or via the U-POL website at WWW.U-POL.COM. U-POL is not responsible for the results obtained by others over whose methods we have no control and thereof U-POL is not liable for consequential or incidental damages including loss of profits.

#### U-POL US, Inc.

108 Commerce Way  
Stockertown, PA 18083  
WWW.U-POL.COM

#### US Sales

T: (610) 746 7081  
F: (610) 743 8654  
sales-us@u-pol.com

#### Rest of the World Sales

T: +44 (0)20 8492 5900  
F: +44 (0)20 8150 5605  
sales@u-pol.com

#### Technical

T: +44 (0)1933 230 310  
F: +44 (0)1933 425 797  
technicaldepartment@u-pol.com

**EMERGENCY TELEPHONE:1-800-424-9300**