

PRODUCT HIGHLIGHTS

4162, 4164

Ultra Flex™ Brushable Seam Sealer

DESCRIPTION:

Ultra Flex Brushable Seam Sealer is a rapid curing, flexible seam sealer designed for all types of painted surfaces, bare metal and primed surfaces. It is resistant to weather exposure and temperature variations. Paintable and sandable. It remains flexible and seals wet or dry. Use to seal seams in floorpans, fire walls, truck seams, wheel wells, etc. Brush marks duplicate original factory finish. Skins in 5 minutes. Air dries in one hour.

PRODUCTS:

- 4162 Ultra Flex™ Brushable Seam Sealer, 11 oz. cartridge (324 ml), 12/case
- 4164 Ultra Flex™ Brushable Seam Sealer, Quart (0.946 L), 6/case



SURFACE PREP:

Clean surface with SCAT (TDS222), Speedi SCAT (TDS223) or Aqua SCAT 2 (TDS225).



MIX RATIO:

Ready to use.



DRY TO PAINT TIME:

Skins in 5 minutes, paintable in 30 minutes.

*See next page for more detailed product application. See website for this document in other languages.
Vea la página siguiente para un uso más detallado del producto. Vea el Web site para este documento en español.
Voir la prochaine page pour une application plus détaillée de produit. Voir le site Web pour ce document en français.*

PRODUCT DATA

4162, 4164

Ultra Flex™ Brushable Seam Sealer

SUITABLE SUBSTRATES:

Painted surfaces, bare metal, and primed surfaces.

SURFACE PREPARATION:

Clean surface with SCAT (TDS222), Speedi SCAT (TDS223) or Aqua SCAT 2 (TDS225).

APPLICATION:

1. Surface must be clean and dry and free from wax or silicone.
2. Brushable Seam Sealer can be applied with an acid brush, or by using the cartridge container and a standard caulking gun.
3. Excess may be cleaned with Acry Solvent (TDS316).



REGULATORY:

Category: Sealant	Individual Component 4162, 4164
VOC Actual	2.82#/gal (338 g/l)
VOC Regulatory	2.82#/gal (338 g/l)
Weight % of Volatiles	25.91%
Weight % of Water	0
Weight % of Exempt Compounds	0
Volume % of Exempt Compounds	0
Density of Material	10.88

ADVANTAGES:

- Skins in 5 minutes.
- Paintable in 30 minutes.
- Contains no asbestos.
- Excellent adhesion to primer or bare metal.
- Flexible.
- Will hold brush marks if desired.

COMPETITION:

3M 08655/08656	Marhyde 7005
CAR/Bernardo Ecenarro PROTEC-BRUSH	Kent 10120
Car System 126.063	Evercoat/Bodymagic 265
Dominon SS 500001	

See website (www.tat-co.com) for this document in other languages.

Vea el Web site (www.tat-co.com) para este documento en español.

Voir le site Web (www.tat-co.com) pour ce document en français.