

Distributed exclusively in North America by:

**US Chemical & Plastics**


A Division of Alco Industries Inc.  
 600 Nova Drive S.E., Massillon, Ohio 44646  
 330-830-6000  
[www.uschem.com](http://www.uschem.com)

1K Spot Blender

Prod. No. 3 680 093

**TECHNOLOGY**

**SprayMax®**



- Spray pattern like a spray gun
- High productivity
- Easy application
- Constant atomization pressure during the total application process
- Finest aerosol dispersion
- Professional paint result

**PRODUCT**

- Ideal product for spot repair and blend-in jobs
- Easy and time-saving application
- Especially suited for clear over base systems and 2K topcoats
- Very good redissolving capacity
- Easy to polish
- Results seamless blend-in-areas

Basis of raw material:

Combination of special resins and solvents

**FIELD OF APPLICATION**

Recommended for:

spot repair and blend-in-jobs

Substrate:

2K clear coats and 2K topcoats

Pre-Treatment:



The old paintwork within the blend-in area should thoroughly be topped off using a P 2000 – P 4000 grit sand paper

## PROCESSING

Protections:



Personal protection is required  
respirator mask type A2/P2




Protective gloves,  
e.g. from latex or nitrile

Spray passes



Apply several light spray passes to the edge of the blend-in-area immediately after application of the 2K clear coat or 2K topcoat to achieve a smooth transition.

Finish:



When work is finished, reverse aerosol and spray valve empty

Disposal:

The emptied aerosols are suitable for household collection.

## CHARACTERISTICS

Solid content: 4.8 % per weight related to active ingredient

VOC value: 6.7 lbs/Gal (766 g/l)

Coverage: approx. 5.4 sq ft (0.5 m<sup>2</sup>) /aerosol can

Degree of gloss: n/a

Shelf life: 60 months / 70 °F (20 °C)

Remarks For professional use only

SprayMax<sup>®</sup> is a registered trade mark of the Peter Kwasny Group.

The information contained in this paper corresponds to our present knowledge and is a guide to our products and their uses. It is not to be understood as a guarantee for certain properties of our products or of their specific applications. The warnings printed on our labels must be respected. Any industrial property rights should be observed.