**Product Name: Everglass quart Product identifier:** 100632 **Revision Date:** 07-18-2015

Replaces:



### 1. Identification

**Product Name: Everglass quart** 

**Product identifier:** 100632

Relevant identified uses of the substance or mixture and uses

advised against:

**ITW Evercoat** Chemical Manufacturer /

Importer / Distributor: a division of Illinois Tool Works Inc.

> 6600 Cornell Road Cincinnati, OH 45242

513-489-7600

**Emergency telephone number:** CHEMTREC: 1-800-424-9300

CANUTEC: 1-613-996-6666

Fiberglass reinforced bodyfiller

#### 2. Hazard(s) identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

**GHS Hazard** Symbols:





**GHS Classification:** Respiratory Sensitisation Category 1

Skin Sensitisation Category 1

Reproductive Toxicity Category 1B

Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 1 Specific Target Organ Systemic Toxicity (STOT) - Repeated Exposure Category 1

Skin Corrosion/Irritation Category 2

Serious Eye Damage/Eye Irritation Category 2A

Germ Cell Mutagenicity Category 2

Carcinogenicity Category 2 Flammable Liquid Category 3

Hazardous to the aquatic environment - Acute Category 3

**GHS Signal Word:** Danger

Flammable liquid and vapour. **GHS Hazard Statements:** 

Causes skin irritation.

May cause an allergic skin reaction.

Product Name: Everglass quart Product identifier: 100632 Revision Date: 07-18-2015

Replaces:

Causes serious eye irritation.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Suspected of causing genetic defects.

Suspected of causing cancer.

May damage fertility or the unborn child.

Causes damage to organs.

Causes damage to organs through prolonged or repeated exposure.

Harmful to aquatic life.

GHS Precautionary Statements: Safety Precautions:

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid breathing dust/fume/gas/mist/vapours/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Contaminated work clothing should not be allowed out of the workplace.

Avoid release to the environment.

Wear protective gloves/protective clothing/eye protection/face protection.

Use personal protective equipment as required.

In case of inadequate ventilation wear respiratory protection.

**First Aid Measures:** IF ON SKIN: Wash with plenty of soap and water.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing.

Rinse skin with water/shower.

IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a

position comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,

if present and easy to do. Continue rinsing.

IF exposed: Call a POISON CENTER or doctor/physician. IF exposed or concerned: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

Specific treatment (see on this label).

If skin irritation occurs: Get medical advice/attention.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

Take off contaminated clothing and wash before reuse.

Wash contaminated clothing before reuse.

In case of fire: Use for extinction.

**Storage:** Keep container tightly closed.

Product Name: Everglass quart Product identifier: 100632 Revision Date: 07-18-2015

Replaces:

Store in a well-ventilated place. Keep cool.

Store locked up.

**Disposal:** Dispose of contents/container in accordance with

local/regional/national/international regulation for hazardous wastes.

Hazards not otherwise

classified:

Reports have associated repeated and prolonged occupational overexposure to

solvents with permanent brain and nervous system damage.

## 3. Composition/information on ingredients

Chemical Component:	CAS number and other unique identifiers	% (or range) of ingredient	
Styrene	100-42-5	10 - 30	
Acid anhydride	85-43-8	0.1 - 1	
Dimethylaniline (DMA)	121-69-7	0.1 - 1	

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. First-aid measures

**Eye Contact:** Flush eyes with plenty of water for at least 20 minutes retracting

eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention. Flush eyes gently with water for at least 15 minutes, lifting upper & lower

eye lids. Seek immediate medical attention.

**Skin Contact:** Wash with soap and water. Get medical attention if irritation

develops or persists. Remove contaminated clothing and continue flushing with water. Wash affected area thoroughly with soap and water. Seek medical advice if symptoms persist Wash clothing

before reuse.

**Inhalation:** Remove to fresh air. If breathing is difficult, have a trained

individual administer oxygen. If not breathing, give artificial respiration and have a trained individual administer oxygen. Get medical attention immediately. If symptoms develop, immediately move individual away from exposure and into fresh air. Get medical attention immediately. Keep the victim warm and quiet. If the victim has stopped breathing open airway, loosen collar and belt, and administer artificial respiration. If breathing is difficult, oxygen may be beneficial if administered by trained personnel, preferably

on a doctor's advice.

**Ingestion:** Do not induce vomiting and seek medical attention immediately.

Drink two glasses of water or milk to dilute. Provide medical care provider with this MSDS. Call a physician or poison control center

Product Name: Everglass quart Product identifier: 100632 Revision Date: 07-18-2015

Replaces:

immediately. Do not induce vomiting unless directed to do so by medical personnel. If individual is drowsy or unconscious, do not give anything by mouth; place individual on left side with head down. If possible, do not leave individual unattended. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs.

Immediate medical attention and special treatment needed,:

No additional first aid information available

### 5. Fire-fighting measures

**Suitable extinguishing media:** Use alcohol resistant foam, carbon dioxide, dry chemical, or water

spray when fighting fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the fire. Do not direct a water stream directly into the hot burning liquid. Regular foam Carbon dioxide Dry

chemical

Unsuitable extinguishing media:

No data available

**Fire and/or Explosion Hazards:** Vapors may be ignited by sparks, flames or other sources of ignition

if material is above the flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition

and flash back.

**Hazardous Combustion** 

**Products:** 

Special protective equipment and precautions for fire-

fighters:

Carbon dioxide, Carbon monoxide, Styrene oxide, Phthalic

anhydride, Hydrocarbons

Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight

fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Water may be used to cool closed containers to prevent pressure build-up and possible auto ignition or explosion when exposed to extreme

heat.

Wear a self contained breathing apparatus (NIOSH approved) with a full face piece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal

protective equipment.

### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Methods and material for containment and cleaning up: No health affects expected from the clean-up of this material if contact can be avoided. Follow personal protective equipment recommendations found in Section VIII of this MSDS

No special spill clean-up considerations. Collect and discard in regular trash. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area. Activate

Product Name: Everglass quart Product identifier: 100632 Revision Date: 07-18-2015

Replaces:

available exhaust ventilation equipment in the immediate spill area. All personnel in the area should be protected as in Section 8. Avoid

breathing vapors. Use an inert absorbent such as sand or vermiculite. Place in properly labeled closed container.

## 7. Handling and storage

**Precautions for safe handling:** Mildly irritating material. Avoid unnecessary exposure. All hazard

precautions given in the data sheet must be observed. Do not get in eyes, on skin and clothing Wash hands before eating Use with adequate ventilation Avoid contact with material, avoid breathing dusts or fumes, use only in a well ventilated area. Do not take internally. Keep container closed when not in use. Keep out of the

reach of children.

**Conditions for safe storage:** Store in a cool dry place. Isolate from incompatible materials. Store

in a cool dry place For maximum product quality, avoid prolonged storage at temperatures above 75 °F (25 °C). Keep away from heat, sparks, and flame Store in a tightly closed container Avoid contact

with incompatible materials.

Materials to Avoid/Chemical

Incompatibility::

Peroxides Strong acids Strong oxidizing agents Polymerization

catalysts

## 8. Exposure controls/personal protection

#### Limits:

Chemical Component	OSHA PEL	ACGIH TLV-TWA	ACGIH STEL	
Styrene	100 ppm	20 ppm	40 ppm STEL; 170 mg/m3	
			STEL	

Appropriate engineering

controls.:

No exposure limits exist for the constituents of this product. Use local exhaust ventilation or other engineering controls to minimize exposures and maintain operator comfort. General or local ventilation or isolation may prove adequate to keep airborne exposures below exposure limits. Explosion proof exhaust

ventilation should be used.

**Eye Protection:** Wear chemically resistant safety glasses with side shields when

handling this product. Do not wear contact lenses. Splash proof chemical goggles are recommended to protect against the splash of

product.

**Skin Protection:** Not normally considered a skin hazard. Where use can result in skin

contact, practice good personal hygiene and wear a barrier cream and/or impervious surgical style gloves. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work. Protective gloves and proper clothing

Page 5 of 9

Product Name: Everglass quart Product identifier: 100632 Revision Date: 07-18-2015

Replaces:

should be worn to prevent skin contact. Gloves should be made of

neoprene or natural rubber. To prevent repeated or prolonged skin

contact, wear impervious clothing and boots

**Respiratory Protection:** Respiratory protection may be required to avoid overexposure

when handling this product. General or local exhaust ventilation is the preferred means of protection. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms. Use

a NIOSH approved respirator designed to remove particulate

matter and organic solvent vapors.

**Other Protective Equipment:** Splash proof chemical goggles are recommended to protect against

the splash of product. Protective gloves and proper clothing should

be worn to prevent skin contact. Gloves should be made of

neoprene or natural rubber. To prevent repeated or prolonged skin

contact, wear impervious clothing and boots

**General Hygiene Conditions:** All hazard precautions given in the data sheet must be observed.

Do not get in eyes, on skin and clothing Wash hands before eating Use with adequate ventilation Avoid contact with material, avoid breathing dusts or fumes, use only in a well ventilated area. Do not take internally. Keep container closed when not in use. Keep out of

the reach of children.

#### 9. Physical and chemical properties

Appearance (physical state):PasteColor:Blue/GreenOdor:Aromatic

**Odor threshold:**No data available

pH: Neutral

Melting Point/Freezing Point (°C):

No data available

Initial Boiling Point and Boiling Range (°C): 145 Flash Point (°C): 49

**Evaporation Rate:**No data available **Flammability (solid, gas):**No data available

Upper Flammable/Explosive Limit: 6.1 Lower Flammable/Explosive Limit: 1.1

Vapor Pressure: 5 MMHG@20C/68F

**Vapor Density:** Heavier than air. Vapors that evolve from this product

will tend to settle and accumulate near the floor.

Relative Density: 1.71
Solubility(ies): Insoluble
Partition coefficient: n-octanol/water: 1.36
Auto-ignition Temperature (°C): 490 °C

Decomposition Temperature::No data availableViscosity:No data available

**VOC (as packaged-less exempts and water)** 1.05 or 127

Page 6 of 9

Product Name: Everglass quart Product identifier: 100632 Revision Date: 07-18-2015

Replaces:

**VOC (as applied\*- 2% by wt hardener- less** 0.52 or 62

exempts and water)

Percent Solids by weight – as packaged 92.60 Percent Solids by weight – as applied\* - 2% 96.30

by wt hardener

VHAP Content by weight – as packaged 12.1 VHAP Content by weight – as applied\* - 2% 5.9

by weight hardener

### 10. Stability and reactivity

**Reactivity:** No data available

**Chemical stability:** Stable under normal conditions.

Conditions to avoid: None known. .

**Incompatible materials:** Peroxides Strong oxidizing agents Polymerization

catalysts

**Hazardous decomposition** 

products:

Carbon dioxide Carbon monoxide Styrene oxide Hydrocarbons

### 11. Toxicological information

Likely routes of exposure (inhalation, ingestion, skin and eye contact):

Ingestion, Skin contact, Eye contact, Absorption

#### <u>Immediate (Acute) Health Effects by Route of Exposure:</u>

**Inhalation Irritation:** Can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and

headache. Excessive inhalation of vapors may cause nasal and respiratory irritation,

acute nervous system depression, fatigue, weakness, nausea, headache and

dizziness.

Airborne overexposure well above the PEL may result additionally in eye irritation,

headache, chemical bronchitis, asthma-like findings or pulmonary edema.

**Skin Contact:** Can cause minor skin irritation, defatting, and dermatitis.

**Skin Absorption:** No absorption hazard in normal industrial use. Causes skin irritation. Contact may

cause irritation and possible dermatitis or sensitization. Symptoms may include

redness, burning, drying and cracking of skin, and skin burns

**Eye Contact:** Can cause moderate irritation, tearing and reddening, but not likely to permanently

injure eye tissue. Contact with liquid or vapor may result in irritation, redness,

tearing, and blurred vision.

**Ingestion Irritation:** Irritating to mouth, throat, and stomach. Can cause abdominal discomfort, nausea,

vomiting and diarrhea. Causes gastrointestinal tract irritation, nausea, vomiting, diarrhea and possible ulcerations to mucous membranes. Aspiration of material into

the lungs can cause chemical pneumonitis which can be fatal.

**Ingestion Toxicity:** Harmful if swallowed. May cause systemic poisoning.

Product Name: Everglass quart Product identifier: 100632 Revision Date: 07-18-2015

Replaces:

**Long-Term (Chronic) Health Effects:** 

**Carcinogenicity:** Suspected of causing cancer. The International Agency for Research on Cancer

(IARC) has classified styrene as a group 2B carcinogen (possibly carcinogenic to

humans).

Reproductive and

May damage fertility or the unborn child.

**Developmental Toxicity:** 

**Mutagenicity:** Suspected of causing genetic defects.

**Inhalation:** Upon prolonged and/or repeated exposure, can cause moderate respiratory

irritation, dizziness, weakness, fatique, nausea and headache.

**Skin Contact:** Upon prolonged or repeated contact, can cause minor skin irritation, defatting, and

dermatitis.

**Skin Absorption:** Upon prolonged or repeated exposure, no hazard in normal industrial use.

Component Toxicology Data

Chemical Component	Oral LD50	Dermal LD50	Inhalation LC50	
No data available				

### Has the chemical been classified as a Carcinogen by NTP, IARC or OSHA.

Chemical Name	OSHA Carcinogen	IARC Carcinogen	NTP Carcinogen	
Styrene	N	Υ	Υ	

#### 12. Ecological information

Ecotoxicity (aquatic and

Toxic to aquatic life. Styrene is toxic to aquatic organisms and should

terrestrial, where available): not be released

to sewage, draining systems or any body of water exceeding

concentrations of approved limits under applicable regulations and

permits.

Persistence and degradability:

Mobility in soil:

No data available No data available

Other adverse effects (such as

No data available

hazardous to the ozone layer):

**Ecological Toxicity Data** 

Ecological Toxicity Data	+		
Chemical Component	Aquatic EC50 Crustacea	Aquatic ERC50 Algae	Aquatic LC50 Fish
No data available			

## 13. Disposal considerations

Description of waste residues: Safe Handling of Waste:

Spent or discarded material is a hazardous waste.

This material as supplied, if discarded, would be not be regulated

as a hazardous waste under RCRA (40 CFR 261).

Product Name: Everglass quart Product identifier: 100632 Revision Date: 07-18-2015

Replaces:

Waste treatment methods (including packaging):

Dispose of by incineration following Federal, State, Local, or

Provincial regulations.

Waste Disposal Code(s):

D001

## 14. Transport information

**UN proper shipping name:** The DOT Classification for shipping is dependent on quantity,

type of packaging (a kit may include other components), or

method of shipment.

#### 15. Regulatory information

**TSCA Status:** The intentional ingredients of this product are listed.

**Regulated Components:** 

Chemical Component	CAS number and other unique identifiers	CERCLA	SARA EHS	SARA 313	California Prop 65
Styrene	100-42-5	N	N	Υ	N

### 16. Other information, including date of preparation or last revision.

**Revision Date:** 07-18-2015

Revision Number: 10

Disclaimer: NOTICE: The information accumulated herein is believed to be correct as of the date issued from sources, which are believed to be accurate and reliable. Since it is not possible to anticipate all circumstances of use, recipients are advised to confirm, in advance of need, that the information is current, applicable and suitable to their circumstances