

Printing date 03/14/2018 Reviewed on 06/28/2017

1 Identification

· Product identifier

· Trade name: 29433 1K Seam Sealer Gun Cleaner

· Article number: 29433

- · Application of the substance / the mixture Instrument cleaner
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

SEM Products Inc. 1685 Overview Drive Rock Hill, SC 29730

803 207 8225

· Information department:

cust_care@semproducts.com : SEM Products,Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT

· Emergency telephone number: CHEMTREC 1-800-424-9300

2 Hazard(s) identification

· Classification of the substance or mixture





GHS02 GHS04 Flame, Gas cylinder

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurized container: May burst if heated.



Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02

02 GHS04

CHCO

- · Signal word Danger
- · Hazard-determining components of labeling:

butanone

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurized container: May burst if heated.

H319 Causes serious eye irritation.H336 May cause drowsiness or dizziness.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P211 Do not spray on an open flame or other ignition source.
P251 Pressurized container: Do not pierce or burn, even after use.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

(Contd. on page 2)



Printing date 03/14/2018 Reviewed on 06/28/2017

Trade name: 29433 1K Seam Sealer Gun Cleaner

(Contd. of page 1)

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear eye protection / face protection.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P312 Call a poison center/doctor if you feel unwell.

P337+P313 If eye irritation persists: Get medical advice/attention.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2 Fire = 4

Reactivity = 3

· HMIS-ratings (scale 0 - 4)

HEALTH 2 FIRE 4

Health = 2Fire = 4

REACTIVITY 3 Reactivity = 3

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description:

Mixture: consisting of the following components.

Weight percentages

· Dangerous o	components:	
<i>78-93-3</i>	butanone	70-100%
68476-86-8	Petroleum gases, liquefied, sweetened	13-30%

4 First-aid measures

- · Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)



Printing date 03/14/2018 Reviewed on 06/28/2017

Trade name: 29433 1K Seam Sealer Gun Cleaner

(Contd. of page 2)

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up: Ensure adequate ventilation.
- · Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:	
78-93-3 butanone	200 ppm
· PAC-2:	
78-93-3 butanone	2700* ppm
· PAC-3:	
78-93-3 butanone	4000* ppm

7 Handling and storage

- · Handling:
- · Precautions for safe handling No special measures required.
- · Information about protection against explosions and fires:

Do not spray on a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurized containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.

(Contd. on page 4)



Printing date 03/14/2018 Reviewed on 06/28/2017

Trade name: 29433 1K Seam Sealer Gun Cleaner

· Specific end use(s) No further relevant information available.

(Contd. of page 3)

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

<i>78-9</i> .	78-93-3 butanone				
PEL	Long-term value: 590 mg/m³, 200 ppm				
REL	Short-term value: 885 mg/m³, 300 ppm Long-term value: 590 mg/m³, 200 ppm				
TLV	Short-term value: 885 mg/m³, 300 ppm Long-term value: 590 mg/m³, 200 ppm BEI				

· Ingredients with biological limit values:

78-93-3 butanone

BEI 2 mg/L

Medium: urine Time: end of shift Parameter: MEK

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

- · Breathing equipment: Not required.
- · Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

SEM

Printing date 03/14/2018 Reviewed on 06/28/2017

Trade name: 29433 1K Seam Sealer Gun Cleaner

· Eye protection:

(Contd. of page 4)



Tightly sealed goggles

· Information on basic physical and chemical properties · General Information					
rorm: Color:	Aerosol				
Cowr: Odor:	According to product specification Characteristic				
Odor threshold:	Not determined.				
pH-value:	Not determined.				
Change in condition					
Melting point/Melting range:	Undetermined.				
Boiling point/Boiling range:	79 °C				
Flash point:	-103 °C				
Flammability (solid, gaseous):	Not applicable.				
Ignition temperature:	514 °C				
Decomposition temperature:	Not determined.				
Auto igniting:	Product is not selfigniting.				
Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.				
Explosion limits:					
Lower:	1.8 Vol %				
Upper:	11.5 Vol %				
Vapor pressure at 20 °C:	105 hPa				
Density at 20 °C:	0.71257 g/cm³				
Relative density	Not determined.				
Vapor density	Not determined.				
Evaporation rate	Not applicable.				
Solubility in / Miscibility with					
Water:	Not miscible or difficult to mix.				
Partition coefficient (n-octanol/wat	t er): Not determined.				
Viscosity:					
Dynamic:	Not determined.				
Kinematic:	Not determined.				

(Contd. on page 6)



Printing date 03/14/2018 Reviewed on 06/28/2017

Trade name: 29433 1K Seam Sealer Gun Cleaner

(Contd. of page 5)

VOC content:	100.00 % 712.6 g/l / 5.95 lb/gl	
Solids content: Other information	0.0% No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC5	· LD/LC50 values that are relevant for classification:		
78-93-3	butano	one	
Oral	LD50	3,300 mg/kg (rat)	
Dermal	LD50	5.000 mg/kg (rabbit)	

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.

(Contd. on page 7)



Printing date 03/14/2018 Reviewed on 06/28/2017

Trade name: 29433 1K Seam Sealer Gun Cleaner

(Contd. of page 6)

- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Aerosols, flammable

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

1 4 0	7		•	C	2 ·
44	rang	nort	m	forma	tion
	LULIUS	u	UUU)	Ullitu	uuuu

777	$J_{-}J$	V	mh	nr

· DOT, ADR, IMDG, IATA UN1950

· UN proper shipping name

 $\cdot DOT$

 $\cdot ADR$ 1950 Aerosols · IMDG **AEROSOLS**

AEROSOLS, flammable \cdot IATA

- · Transport hazard class(es)
- $\cdot DOT$



· Class 2.1 2.1

· Label

 $\cdot ADR$



Class 2 5F Gases

(Contd. on page 8)

SEM

Printing date 03/14/2018 Reviewed on 06/28/2017

Trade name: 29433 1K Seam Sealer Gun Cleaner

	(Contd. of page
Label	2.1
IMDG, IATA	
Class	2.1
Label	2.1
Packing group DOT, ADR, IMDG, IATA	Void
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Warning: Gases
EMS Number:	F-D,S-U
Stowage Code	SW1 Protected from sources of heat.
· ·	SW22 For AEROSOLS with a maximum capacity of 1 litr
	Category A. For AEROSOLS with a capacity above 1 litr
	Category B. For WASTE AEROSOLS: Category C, Clear of living
	quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litr Segregation as for class 9. Stow "separated from" class 1 except f division 1.4. For AEROSOLS with a capacity above 1 litr Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
Transport in bulk according to Annex	
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 75 kg
	On cargo aircraft only: 150 kg
ADR	
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
	1 2 1

USA

Printing date 03/14/2018 Reviewed on 06/28/2017

Trade name: 29433 1K Seam Sealer Gun Cleaner

(Contd. of page 8)

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

78-93-3 butanone

· TSCA (Toxic Substances Control Act):

78-93-3 butanone

· TSCA new (21st Century Act) (Substances not listed)

68476-86-8 Petroleum gases, liquefied, sweetened

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- · Cancerogenity categories
- · EPA (Environmental Protection Agency)

78-93-3 butanone

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02

GHS04

· Signal word Danger

GHS07

· Hazard-determining components of labeling:

butanone

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurized container: May burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

(Contd. on page 10)

Printing date 03/14/2018 Reviewed on 06/28/2017

Trade name: 29433 1K Seam Sealer Gun Cleaner

(Contd. of page 9)

P211 Do not spray on an open flame or other ignition source. P251 Pressurized container: Do not pierce or burn, even after use. P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear eye protection / face protection.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P312 Call a poison center/doctor if you feel unwell.

P337+P313 If eye irritation persists: Get medical advice/attention.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: Rita Joiner (rjoiner@semproducts.com)
- · Date of preparation / last revision 03/14/2018 / 8
- · Abbreviations and acronvms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Aerosol 1: Aerosols - Category 1

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

* Data compared to the previous version altered.