

# **Material Safety Data Sheet**

# 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Identification** 

Product ID: DP23

Product Name: \*DO\* EGYPTIAN GOLD PEARL DP-23

Product Use:
Print date:
None specified.
31/Mar/2013
Revision Date:
28/Feb/2013

Company Identification
The Valspar Corporation

PO Box 1461

Minneapolis, MN 55440

**Manufacturer's Phone:** 1-612-851-7000

24-Hour Medical Emergency 1-8

Phone:

1-888-345-5732

## 2. HAZARDS IDENTIFICATION

## **Primary Routes of Exposure:**

Inhalation Ingestion Skin absorption

### **Eye Contact:**

· Moderate eye irritation

#### **Skin Contact:**

· Causes skin irritation.

# Ingestion:

• Irritation of the mouth, throat, and stomach.

#### Inhalation:

May cause irritation of respiratory tract.

# **Target Organ and Other Health Effects:**

· Causes headache, drowsiness or other effects to the central nervous system.

# This product contains ingredients that may contribute to the following potential chronic health effects:

- Prolonged breathing of mica dust may produce pneumoconiosis.
- Prolonged exposure over TLV may produce pneumoconiosis.

#### Carcinogens:

· Possible cancer hazard. Contains material which may cause cancer based on animal data.

# 3. COMPOSITION / INFORMATION ON HAZARDOUS INGREDIENTS

Ingredient Name CAS-No.	Approx. Weight %	Chemical Name
TITANIUM DIOXIDE 13463-67-7	45 - 50	Titanium dioxide
PROPRIETARY INERT	30 - 35	PROPRIETARY INERT
PROPYLENE GLYCOL MONO PROPYL ETHER 1569-01-3	5 - 10	2-Propanol, 1-propoxy-
PROPRIETARY COLOR PIGMENT	1 - 5	PROPRIETARY COLOR PIGMENT

If this section is blank there are no hazardous components per OSHA guidelines.

#### 4. FIRST AID MEASURES

# **Eye Contact:**

Get medical attention, if symptoms develop or persist. Immediately flush eye(s) with plenty of water. Remove any contact lenses and open eyes wide apart.

## **Skin Contact:**

Remove contaminated clothing and shoes. Wash off immediately with plenty of water for at least 15 minutes. Get medical attention, if symptoms develop or persist.

#### Ingestion:

Rinse mouth with water. Give one or two glasses of water. Only induce vomiting at the instruction of medical personnel. Get medical attention.

#### Inhalation:

Move to fresh air. Get medical attention, if symptoms develop or persist.

# Medical conditions aggravated by exposure:

Any respiratory or skin condition.

# 5. FIRE FIGHTING MEASURES

Flash point (Fahrenheit): 118
Flash point (Celsius): 48
Lower explosive limit (%): 1
Upper explosive limit (%): 17

Autoignition temperature: not determined

Sensitivity to impact: no

# 5. FIRE FIGHTING MEASURES

Sensitivity to static discharge:

Hazardous combustion products:

Can be sensitive to static discharge hazards. Please see bonding and grounding information in Section 7. See Section 10.

#### Unusual fire and explosion hazards:

None known.

# **Extinguishing media:**

Carbon dioxide, dry chemical, foam and/or water fog.

#### Fire fighting procedures:

Firefighters should be equipped with self-contained breathing apparatus and turn out gear. Keep containers and surroundings cool with water spray.

# 6. ACCIDENTAL RELEASE MEASURES

## Action to be taken if material is released or spilled:

Ventilate the area. Avoid breathing dust or vapor. Use self-containing breathing apparatus or airmask for large spills in a confined area. Wipe, scrape or soak up in an inert material and put in a container for disposal. See section 7, "Handling and Storage", for proper container and storage procedures. Remove all sources of ignition. Soak up with inert absorbent material. Use only non-sparking tools. Avoid contact with eyes.

# 7. HANDLING AND STORAGE

#### Precautions to be taken in handling and storage:

Keep away from heat, sparks and open flame. - No smoking. Keep container closed when not in use. Do not store above 120 degrees F. (49 degrees C). Based on flash point and vapor pressure, suitable storage should be provided in accordance with OSHA regulation 1910.106, Ontario OH&S regulation 851 section 22. Empty containers may contain product residue, including flammable or explosive vapors. Do not cut, puncture or weld on or near container. All label warnings must be observed until the container has been commercially cleaned or reconditioned. If the product is used near or above the flashpoint, an ignition hazard may be present. Activities, uses, or operations which liberate vapor (such as mixing or free fall of liquids) may also present an ignition hazard. Please ensure containers and other interconnected equipment are properly bonded and grounded at all times.

# 8. PERSONAL PROTECTIVE EQUIPMENT AND EXPOSURE CONTROLS

### **Personal Protective Equipment**

#### Eye and face protection:

Wear safety glasses or goggles to protect against exposure.

#### Skin protection:

Appropriate chemical resistant gloves should be worn.

### **Other Personel Protection Data:**

Usual industrial work clothes.

#### Respiratory protection:

If exposure cannot be controlled below applicable limits, use the appropriate NIOSH approved respirator such as an air purifying respirator with organic vapor cartridge and dust/mist filter. Consult the respirator manufacturer's literature to ensure that the respirator will provide adequate protection. Read and follow all respirator manufacturer's instructions.

### Ventilation

Use only in well-ventilated areas. Ovens used for curing should contain a fresh air purge to prevent vapours from accumulating and creating a possible explosive mixture. Ensure adequate ventilation, especially in confined areas. Where the product is used in a hazardous classified area, use explosion-proof electrical/ventilating/lighting/equipment.

#### **Exposure Guidelines**

# **OSHA Permissible Exposure Limits (PEL's)**

Ingredient Name CAS-No.	Approx. Weight %	TWA (final)	Ceilings limits (final)	Skin designations
TITANIUM DIOXIDE 13463-67-7	45 - 50	15 mg/m³ TWA dust total		
PROPRIETARY INERT	30 - 35	20 mppcf (<1% crystalline silica)		
PROPRIETARY COLOR PIGMENT	1 - 5	10 mg/m³ TWA fume		

# **ACGIH Threshold Limit Value (TLV's)**

Ingredient Name CAS-No.	Approx. Weight %	TWA	STEL	Ceiling limits	Skin designations
TITANIUM DIOXIDE 13463-67-7	45 - 50	10 mg/m³ TWA			
PROPRIETARY INERT	30 - 35	3 mg/m³ TWA respirable fraction			
PROPRIETARY COLOR PIGMENT	1 - 5	5 mg/m³ TWA respirable fraction			

# 9. PHYSICAL PROPERTIES

Odor: Normal for this product type.

Physical State: powder

pH: not determined

Vapor pressure: 1.7067669 mmHg @ 68°F (20°C)

Vapor density (air = 1.0):

Boiling point: 302°F (150°C)
Solubility in water: Slight (0.1 to 1.0%)
Coefficient of water/oil distribution:

Coefficient of water/oil distribution: not determined
Density (lbs per US gallon): 22.49

Specific Gravity:

Evaporation rate (butyl acetate = 1.0):

Flash point (Fahrenheit):

Flash point (Celsius):

Lower explosive limit (%):

Upper explosive limit (%):

17

Autoignition temperature: not determined

# 10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to Avoid: Heat.

Incompatibility: Strong oxidizing agents Acids or alkalies.

Hazardous Polymerization: None anticipated.

Hazardous Decomposition Products: Silicon dioxide. Carbon monoxide and carbon dioxide.

Metal oxide fumes.

Sensitivity to static discharge: Can be sensitive to static discharge hazards. Please see

bonding and grounding information in Section 7.

# 11. TOXICOLOGICAL INFORMATION

0	Approx. Weight %	NIOSH - Selected LD50s and LC50s
TITANIUM DIOXIDE 13463-67-7	45 - 50	> 10000 mg/kg Oral LD50 Rat
PROPYLENE GLYCOL MONO PROPYL ETHER 1569-01-3		= 2504 mg/kg Oral LD50 Rat = 3550 mg/kg Dermal LD50 Rabbit
PROPRIETARY COLOR PIGMENT	1 - 5	> 10000 mg/kg Oral LD50 Rat

#### Mutagens/Teratogens/Carcinogens:

Possible cancer hazard. Contains material which may cause cancer based on animal data.

Contains TIO2 which is listed by IARC as a possible human carcinogen (Group 2B) based on animal data. Neither long term animal studies, nor human epidemiology studies of workers exposed to TIO2 provide an adequate basis to conclude TIO2 is carcinogenic. TIO2 is not classified as a carcinogen by NTP, U.S. OSHA, or the U.S. EPA.

Ingredient Name	Approx.		IARC Group 2A - Limited	•
CAS-No.	Weight %	Evidence	Human Data	Sufficient Animal Data
TITANIUM DIOXIDE	45 - 50			Monograph 47 [1989]
13463-67-7				

0	Approx. Weight %	OSHA - Hazard Communication Carcinogens	OSHA - Specifically Regulated Carcinogens	ACGIH Carcinogens
TITANIUM DIOXIDE 13463-67-7	45 - 50	Present		

#### 12. ECOLOGICAL DATA

No information on ecology is available.

# 13. DISPOSAL CONSIDERATIONS

Disposal should be made in accordance with federal, state and local regulations.

# 14. TRANSPORTATION INFORMATION

# **U.S. Department of Transportation**

Proper Shipping Name: PIGMENT, NOT REGULATED

# U.S Hazmat and/or International DG shipment exceptions

The supplier may apply one of the following exceptions: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

# **Reportable Quantity Description:**

International Air Transport Association (IATA):

Proper shipping name: NOT REGULATED

**International Maritime Organization (IMO):** 

Proper shipping name: NOT REGULATED

Marine Pollutant No

# 15. REGULATORY INFORMATION

# U.S. FEDERAL REGULATIONS: SARA 311/312 Hazard Class:

Acute: yes
Chronic: yes
Flammability: yes
Reactivity: no
Sudden Pressure: no

#### **U.S. STATE REGULATIONS:**

## Right to Know:

The specific chemical identity of a component may be withheld as a trade secret under 34 Pennsylvania Code, Chapter 317.

# Pennsylvania Right To Know:

PROPRIETARY INERT Trade Secret
PROPRIETARY COLOR PIGMENT Trade Secret

TITANIUM DIOXIDE 13463-67-7

PROPYLENE GLYCOL MONO PROPYL ETHER 1569-01-3

Rule 66 status of product Not photochemically reactive.

# **INTERNATIONAL REGULATIONS - Chemical Inventories**

## **US TSCA Inventory:**

All components of this product are in compliance with U.S. TSCA Chemical Substance Inventory Requirements.

#### **Canada Domestic Substances List:**

All components of this product are listed on the Domestic Substances List.

#### 16. OTHER INFORMATION

**HMIS Codes** 

Health: 2 Flammability: 2 Reactivity: 0

PPE: X - See Section 8 for Personal Protective Equipment (PPE).

#### Abbreviations:

OSHA - Occupational Safety and Health Administration, IARC - International Agency for Research on Cancer, NIOSH - National Institute of Occupational Safety and Health, NTP - National Toxicology Program, ACGIH - American Conference of Governmental Industrial Hygienists, SCAQMD - South Coast Air Quality Management District, TSCA - Toxic Substances Control Act, IATA - International Air Transport Association, IMO - International Maritime Organization, DOT - Department of Transportation, NA - Not applicable, NOT ESTAB - Not established, N.A.V. - Not available, RQ - Reportable quantity, WT - Weight, MG/CU M - Milligrams per cubic meter, G/L - Grams per liter, MM - Millimeters, MPPCF - Millions of particles per cubic foot, PPM - parts per million, PPT - parts per thousand, TCC/PM - Tag closed cup / Pensky-Martens, PB - Lead, PEL - Permissible exposure level, TWA - Time Weighted Average, STEL - Short term exposure limit, C - Celsius, F - Fahrenheit.

#### Disclaimer:

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option. This MSDS contains additional information required by the state of Pennsylvania.

# **Preparation Information:**

Prepared By: Regulatory Affairs Department

Print date: 31/Mar/2013 Revision Date: 28/Feb/2013