

38403 BLENZ-IN

TECHNICAL DATA SHEET

Description

38403 BLENZ-IN is a blending solvent designed to melt the edge of 2K urethane topcoat repairs. 38403 enables the user to keep repairs to a single panel and create an invisible blend.

Features

- > Seamless blends
- Convenient aerosol package
- > Use with both MS and HS clear coats

- 100% UV stable
- Saves time and money

Typical Properties

Handling and Application

MIXING: Shake well before using.



APPLICATION:



Immediately after the last coat of urethane or clear coat has been applied, spray 1-2 light mist coats of **38403** over the blend edge, holding the can 8-10" from the surface. Allow **38403** to dry overnight before polishing the blended area.

NOTE: If clogging develops, remove spray button with a twisting motion and clean with material compliant with VOC regulations in your area. Do not stick pin or other object into can. Gently replace spray button with top of can and spray button pointed away from you.

NOTE: After each use, turn can upside down and spray several seconds to clear spray tip.

STORAGE:



38403 BLENZ-IN should be stored in a cool dry place with adequate ventilation away from heat, sparks and flames. The shelf life for 38403 is 5 years when stored under normal conditions.

TECHNICAL CONSULTATION SERVICE

Our Technical Staff is ready to assist you with any questions. You are invited to take advantage of our extensive experience, laboratory services and trained field service representatives. Call (800) 831-1122 for answers to your questions. Hours of operation are Monday through Thursday 8:00 am until 5:00 pm EST and on Friday 8:00 am until 4:30 pm EST.

DISCLAIMER: The information supplied in this document is for guidance only and should not be construed as a warranty. All implied warranties are expressly disclaimed. All users of the materials are responsible for assuring that it is suitable for their needs, environment and use. All data subject to change as SEM deems appropriate.

Users should review the Material Safety Data Sheet (MSDS) and product label for the material to determine possible health hazards, appropriate engineering controls and precautions to be observed in using the material. Copies of the MSDS and product label are available upon request.