



Reviewed on 08/14/2014

1 Identification

- · Product identifier
- · Trade name: 68442 Mini-Max Clear Fast Set Adhesive
- Article number: 68442
- *Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.*
- · Application of the substance / the mixture Coating

Details of the supplier of the safety data sheet
Manufacturer/Supplier: SEM Products Inc. 1685 Overview Drive Rock Hill, SC 29730 803 207 8225

• Information department:

cust_care@semproducts.com : SEM Products,Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT

• Emergency telephone number: CHEMTREC 1-800-424-9300

2 Hazard(s) identification

· Classification of the substance or mixture



GHS06 Skull and crossbones

Acute Tox. 3 H311 Toxic in contact with skin.



Skin Corr. 1B H314 Causes severe skin burns and eye damage.



Acute Tox. 4	H302 Harmful if swallowed.
Acute Tox. 4	H332 Harmful if inhaled.
Skin Sens. 1	H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

· Label elements

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

(Contd. on page 2)

USA

Printing date 08/14/2014

SEM Reviewed on 08/14/2014

Trade name: 68442 Mini-Max Clear Fast Set Adhesive

25085-99-8 BISPHENOL A EPOXY RESIN

TERTIARY AMINE

		(Contd. of page 1)
Hazard.	determining components of labeling:	
	AINE POLYMERCAPTAN EPOXY HARDENER	
	NOL F EPOXY RESIN	
	RY AMINE	
	NOL A EPOXY RESIN	
	statements	
	1332 Harmful if swallowed or if inhaled.	
H302 + H H311	Toxic in contact with skin.	
H314	Causes severe skin burns and eye damage.	
H317 H317	May cause an allergic skin reaction.	
H335	May cause an anergic skin reaction. May cause respiratory irritation.	
	onary statements	
P260	Do not breathe dust/fume/gas/mist/vapours/spray.	
		d alathing Dinga skin
P303+P3	361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminate with water/shower.	a cioining. Kinse skin
D205 L D		and contract long on if
P303+P3	351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Rem	ove contact tenses, ij
האכת	present and easy to do. Continue rinsing.	
P361	Remove/Take off immediately all contaminated clothing.	
P405 P501	Store locked up.	
P301	Dispose of contents/container in accordance with local/regional/n	ational/international
<u> </u>	regulations.	
	ation system: atings (scale 0 - 4)	
HMIS-ra	Fire = 1 Reactivity = 0 atings (scale 0 - 4)	
HEALTH		
	$\frac{2}{2} Health = 2$	
FIRE	1 $Fire = 1$	
REACTIVI	$\mathbf{rr} \mathbf{O} Reactivity = 0$	
Other ha	neanda	
	pf PBT and vPvB assessment	
	of applicable.	
	ot applicable.	
VEVD: INC	n upplicable.	
Commo	atten lin formention on in one diante	
Compo	sition/information on ingredients	
Chomica	I characterization: Mixtures	
Descripti		
	consisting of the following components.	
	vercentages	
	ous components:	
Dungero	-	40 6007
	POLYAMINE POLYMERCAPTAN EPOXY HARDENER	40 - 60%
28064-14	4-4 BISPHENOL F EPOXY RESIN	30 - 40%

1.5 - 5% (Contd. on page 3) USA

10 -13%



SEM

Reviewed on 08/14/2014

Trade name: 68442 Mini-Max Clear Fast Set Adhesive

2530-83-8 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane

 $\frac{\text{(Contd. of page 2)}}{\leq 1\%}$

4 First-aid measures

- · Description of first aid measures
- · General information:
- Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation:
- Supply fresh air and to be sure call for a doctor.
- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- *Indication of any immediate medical attention and special treatment needed No further relevant information available.*

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- *Methods and material for containment and cleaning up: Use neutralizing agent.*

Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

- · Reference to other sections
- See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Precautions for safe handling
- No special measures required.
- Thorough dedusting.

Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 4)

USA

Page 3/10

Printing date 08/14/2014

Reviewed on 08/14/2014

(Contd. of page 3)

Trade name: 68442 Mini-Max Clear Fast Set Adhesive

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.
- 8 Exposure controls/personal protection
- Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. · Breathing equipment:
- In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- · Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5) USA Printing date 08/14/2014

Reviewed on 08/14/2014

SEM

Trade name: 68442 Mini-Max Clear Fast Set Adhesive

· Eye protection:

(Contd. of page 4)



Tightly sealed goggles

*

9 Physical and chemical properties

General Information	
Appearance:	1::1
Form: Color:	Liquid According to product specification
Odor:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not applicable.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Undetermined.
Flash point:	94 °C
Flammability (solid, gaseous):	Not determined.
Ignition temperature:	
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product does not present an explosion hazard. In use, may form flammable/explosive vapour-air mixture.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapor pressure:	Not applicable.
Density at 20 °C:	1.13486 g/cm ³
Relative density	Not determined.
Vapour density	Not applicable.
Evaporation rate	Not applicable.
Solubility in / Miscibility with Water:	Insoluble.
Partition coefficient (n-octanol/wa	ter): Not determined.
Viscosity:	
Dynamic:	Not applicable.
Kinematic:	Not applicable.
Solvent content:	
Organic solvents:	0.0 %



Reviewed on 08/14/2014

(Contd. of page 5)

Trade name: 68442 Mini-Max Clear Fast Set Adhesive

Solids content: • Other information 100.0 %

No further relevant information available.

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

· Acute toxicity:

• Primary irritant effect:

- on the skin: Caustic effect on skin and mucous membranes.
- on the eye: Strong caustic effect.
- Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

64-17-5 ethanol

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- *Persistence and degradability* No further relevant information available.
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- · Additional ecological information:
- General notes: Water hazard class 1 (Self-assessment): slightly hazardous for water

(Contd. on page 7)

1

USA



Page 7/10

Reviewed on 08/14/2014

Printing date 08/14/2014

Trade name: 68442 Mini-Max Clear Fast Set Adhesive

(Contd. of page 6)

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

- · Recommendation:
- Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packagings:

*

• Recommendation: Disposal must be made according to official regulations.

UN-Number	
DOT, ADR, IMDG, IATA	UN1760
UN proper shipping name	
DOT	Corrosive liquids, n.o.s. (POLYAMINE POLYMERCAPTAN EPO) HARDENER, 3-aminopropyltriethoxysilane)
ADR	1760 Corrosive liquids, n.o.s. (POLYAMINE POLYMERCAPTA EPOXY HARDENER, 3-aminopropyltriethoxysilane)
· IMDG, IATA	CORROSIVE LIQUID, N.O.S. (POLYAMINE POLYMERCAPTA EPOXY HARDENER, 3-aminopropyltriethoxysilane)
Transport hazard class(es)	
DOT	
Class Label	8 Corrosive substances 8
ADR, IMDG, IATA	
and the second s	
Class	8 Corrosive substances
Label	8
Packing group DOT, ADR, IMDG, IATA	111

Printing date 08/14/2014

Reviewed on 08/14/2014

MER

Trade name: 68442 Mini-Max Clear Fast Set Adhesive

	(Contd. of page
· Special precautions for user	Warning: Corrosive substances
· EMS Number:	F-A,S-B
· Segregation groups	Alkalis
• Transport in bulk according to Annex	II of
MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
·DOT	
· Quantity limitations	On passenger aircraft/rail: 5 L
	On cargo aircraft only: 60 L
· Remarks	ORM-D 49CFR 173-150,156,306
· ADR	
\cdot Excepted quantities (EQ)	Code: El
	Maximum net quantity per inner packaging: 30 g
	Maximum net quantity per outer packaging: 1000 g
· IMDG	
· Limited quantities (LQ)	5L
\cdot Excepted quantities (EQ)	Code: El
	Maximum net quantity per inner packaging: 30 g
	Maximum net quantity per outer packaging: 1000 g
· UN ''Model Regulation'':	UN1760, Corrosive liquids, n.o.s. (POLYAMIN
-	POLYMERCAPTAN ÉPOXY HARDENER, 3 aminopropyltriethoxysilane), 8, III

15 Regulatory information

*

· Safety, health and environmental regulations/legislation specific for the substance or mixture · Sara

None of the	ingredient is listed.	
Section 313	(Specific toxic chemical listings):	
67-56-1 me	ethanol	
TSCA (Tox	ic Substances Control Act):	
28064-14-4	BISPHENOL F EPOXY RESIN	
25085-99-8	BISPHENOL A EPOXY RESIN	
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	
919-30-2	3-aminopropyltriethoxysilane	
67-56-1	methanol	
64-17-5	ethanol	
Proposition	65	
Chemicals I	known to cause cancer:	
28064-14-4	BISPHENOL F EPOXY RESIN	
25085-99-8	BISPHENOL A EPOXY RESIN	
	(Contd. c	on page



Printing date 08/14/2014

Reviewed on 08/14/2014

Trade name: 68442 Mini-Max Clear Fast Set Adhesive

 \cdot Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

67-56-1 methanol

64-17-5 ethanol

· Cancerogenity categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

• TLV (Threshold Limit Value established by ACGIH)

64-17-5 ethanol

· NIOSH-Ca (National Institute for Occupational Safety and Health)

67-56-1 methanol

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*




· Signal word Danger

· Hazard-	letermining components of labeling:
POLYAN	IINE POLYMERCAPTAN EPOXY HARDENER
BISPHE	NOL F EPOXY RESIN
TERTIAL	RY AMINE
BISPHE	NOL A EPOXY RESIN
· Hazard s	tatements
H302+H	332 Harmful if swallowed or if inhaled.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.
· Precauti	onary statements
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P303+P.	361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P.	351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P361	Remove/Take off immediately all contaminated clothing.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
· Chemica	l safety assessment: A Chemical Safety Assessment has not been carried out.
	USA

(Contd. on page 10)

(Contd. of page 8)

A3





Reviewed on 08/14/2014

Trade name: 68442 Mini-Max Clear Fast Set Adhesive

(Contd. of page 9)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: Steve Gaver
- · Date of preparation / last revision 08/14/2014 / 1
- · Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organization ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) Acute Tox. 4: Acute toxicity, Hazard Category 4 Acute Tox. 3: Acute toxicity, Hazard Category 3 Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B Skin Sens. 1: Sensitisation - Skin, Hazard Category 1 STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3 \cdot * Data compared to the previous version altered. USA