



3837() SEM SOLVE

TECHNICAL DATA SHEET

Description

3837() SEM SOLVE is a special combination of solvents formulated to simplify cleanup of adhesives, waxes, road tar, grease, oil and paint overspray.

Features

- Removes contaminants fast
- Leaves a clean surface
- Does not leave sticky residue
- 3 convenient sizes

Typical Properties

| | |
|--|--|
| Containers | 38371 gallon, 38374 quart and 38373 aerosol |
| Color | Clear |
| Actual VOC 38373 | 5.94 #/gl (712.8 g/l) |
| Actual VOC 38374 and 38371 | 6.44 #/gl (773.2 g/l) |

Check local VOC regulations to ensure compliance in your area.

Handling and Application

APPLICATION: Apply **3837() SEM SOLVE** liberally to a clean, soft, lint free cloth. Wipe surface to be cleaned in one direction to avoid contamination. Follow with a clean, dry cloth, changing cloths frequently. **DO NOT** leave solvent cloth on painted surface. **DO NOT** use on raw plastic.



STORAGE:



3837() SEM SOLVE should be stored in a cool dry place with adequate ventilation away from heat, sparks and flames. The shelf life for **38373** is 5 years when stored under normal conditions, while the shelf life for **38374** and **38371** is unlimited.

TECHNICAL CONSULTATION SERVICE

Our Technical Staff is ready to assist you with any questions. You are invited to take advantage of our extensive experience, laboratory services and trained field service representatives. Call (800) 831-1122 for answers to your questions. Hours of operation are Monday through Thursday 8:00 am until 5:00 pm EST and on Friday 8:00 am until 4:30 pm EST.

DISCLAIMER: The information supplied in this document is for guidance only and should not be construed as a warranty. All implied warranties are expressly disclaimed. All users of the materials are responsible for assuring that it is suitable for their needs, environment and use. All data subject to change as SEM deems appropriate.

Users should review the Material Safety Data Sheet (MSDS) and product label for the material to determine possible health hazards, appropriate engineering controls and precautions to be observed in using the material. Copies of the MSDS and product label are available upon request.