

## 1 Identification

- **Product identifier**
- **Trade name:** 39650 (3965A & 3963B catalyzed)
- **Article number:** 39650 Kit
- **Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Application of the substance / the mixture** Coating
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
SEM Products Inc.  
1685 Overview Drive  
Rock Hill, SC 29730  
803 207 8225
- **Information department:**  
cust\_care@semproducts.com : SEM Products, Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT
- **Emergency telephone number:** CHEMTREC 1-800-424-9300

## 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Carc. 2 H351 Suspected of causing cancer.

STOT SE 2 H371-H335 May cause damage to organs. May cause respiratory irritation.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS07



GHS08

Trade name: 39650 (3965A & 3963B catalyzed)

(Contd. of page 1)

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

HDI Prepolymer

Talc

POLYESTER RESIN

heptan-2-one

· **Hazard statements**

H225 *Highly flammable liquid and vapor.*

H302 *Harmful if swallowed.*

H315 *Causes skin irritation.*

H319 *Causes serious eye irritation.*

H334 *May cause allergy or asthma symptoms or breathing difficulties if inhaled.*

H317 *May cause an allergic skin reaction.*

H351 *Suspected of causing cancer.*

H371-H335 *May cause damage to organs. May cause respiratory irritation.*

· **Precautionary statements**

P210 *Keep away from heat/sparks/open flames/hot surfaces. - No smoking.*

P241 *Use explosion-proof electrical/ventilating/lighting/equipment.*

P303+P361+P353 *IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.*

P305+P351+P338 *IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*

P405 *Store locked up.*

P501 *Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 2

Fire = 3

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = \*2

Fire = 3

Reactivity = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

### 3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:**

Mixture: consisting of the following components.

Weight percentages

· **Dangerous components:**

14807-96-6 Talc

13 - 30%

(Contd. on page 3)



Trade name: 39650 (3965A & 3963B catalyzed)

(Contd. of page 2)

28182-81-2	HDI Prepolymer	13 - 30%
	ACRYLIC RESIN	13 - 30%
67-64-1	acetone	7 - 10%
	POLYESTER RESIN	7 - 10%
	POLYESTER RESIN	7 - 10%
123-86-4	n-butyl acetate	5 - 7%
110-43-0	heptan-2-one	1.5 - 5%

#### 4 First-aid measures

- **Description of first aid measures**
- **General information:**  
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**  
Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Immediately call a doctor.
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

#### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

#### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.

(Contd. on page 4)



Trade name: 39650 (3965A & 3963B catalyzed)

(Contd. of page 3)

See Section 13 for disposal information.

## 7 Handling and storage

- **Precautions for safe handling**  
No special measures required.  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
Keep receptacle tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

## \* 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

**67-64-1 acetone**

PEL	Long-term value: 2400 mg/m <sup>3</sup> , 1000 ppm
REL	Long-term value: 590 mg/m <sup>3</sup> , 250 ppm
TLV	Short-term value: (1782) NIC-1187 mg/m <sup>3</sup> , (750) NIC-500 ppm Long-term value: (1188) NIC-594 mg/m <sup>3</sup> , (500) NIC-250 ppm BEI

**123-86-4 n-butyl acetate**

PEL	Long-term value: 710 mg/m <sup>3</sup> , 150 ppm
REL	Short-term value: 950 mg/m <sup>3</sup> , 200 ppm Long-term value: 710 mg/m <sup>3</sup> , 150 ppm
TLV	Short-term value: 950 mg/m <sup>3</sup> , 200 ppm Long-term value: 713 mg/m <sup>3</sup> , 150 ppm

**110-43-0 heptan-2-one**

PEL	Long-term value: 465 mg/m <sup>3</sup> , 100 ppm
REL	Long-term value: 465 mg/m <sup>3</sup> , 100 ppm
TLV	Long-term value: 233 mg/m <sup>3</sup> , 50 ppm

(Contd. on page 5)

Trade name: 39650 (3965A & 3963B catalyzed)

(Contd. of page 4)

· **Ingredients with biological limit values:**

**67-64-1 acetone**

BEI	50 mg/L
	Medium: urine
	Time: end of shift
	Parameter: Acetone (nonspecific)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

**9 Physical and chemical properties**

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Liquid
Color:	According to product specification
Odor:	Characteristic
Odour threshold:	Not determined.

(Contd. on page 6)



Trade name: 39650 (3965A & 3963B catalyzed)

(Contd. of page 5)

· <b>pH-value:</b>	Not determined.
· <b>Change in condition</b>	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Undetermined.
· <b>Flash point:</b>	-19 °C
· <b>Flammability (solid, gaseous):</b>	Not applicable.
· <b>Ignition temperature:</b>	370 °C
· <b>Decomposition temperature:</b>	Not determined.
· <b>Auto igniting:</b>	Product is not selfigniting.
· <b>Danger of explosion:</b>	In use, may form flammable/explosive vapour-air mixture.
· <b>Explosion limits:</b>	
Lower:	2.6 Vol %
Upper:	13.0 Vol %
· <b>Vapor pressure at 20 °C:</b>	233 hPa
· <b>Density at 20 °C:</b>	1.21 g/cm <sup>3</sup>
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with Water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
Dynamic:	Not determined.
Kinematic:	Not determined.
· <b>Solvent content:</b>	
Organic solvents:	22.1 %
VOC content:	12.1 %
	173.4 g/l / 1.45 lb/gl
Solids content:	72.3 %
· <b>Other information</b>	No further relevant information available.

## 10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

USA

(Contd. on page 7)



Trade name: 39650 (3965A & 3963B catalyzed)

(Contd. of page 6)

## 11 Toxicological information

· **Information on toxicological effects**

· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

### 28182-81-2 HDI Prepolymer

Oral	LD50	1000 mg/kg (rat)
Dermal	LD50	5000 mg/kg (rabbit)
Inhalative	LC50/4 h	137-1150 mg/l (rat)

· **Primary irritant effect:**

· **on the skin:** Irritant to skin and mucous membranes.

· **on the eye:** Irritating effect.

· **Sensitization:**

Sensitization possible through inhalation.

Sensitization possible through skin contact.

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Irritant

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

14807-96-6	Talc	2B
1330-20-7	xylene	3

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

## 12 Ecological information

· **Toxicity**

· **Aquatic toxicity:** No further relevant information available.

· **Persistence and degradability:** No further relevant information available.

· **Bioaccumulative potential:** No further relevant information available.

· **Mobility in soil:** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects:** No further relevant information available.



Trade name: 39650 (3965A & 3963B catalyzed)

(Contd. of page 7)

### 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

· <b>UN-Number</b> · <b>DOT, ADR, IMDG, IATA</b>	UN1992
· <b>UN proper shipping name</b> · <b>DOT</b> · <b>ADR</b> · <b>IMDG, IATA</b>	Flammable liquids, toxic, n.o.s. (Acetone, HDI Prepolymer) 1992 Flammable liquids, toxic, n.o.s. (Acetone, HDI Prepolymer) FLAMMABLE LIQUID, TOXIC, N.O.S. (ACETONE, HDI Prepolymer)
· <b>Transport hazard class(es)</b> · <b>DOT</b>	
	
· <b>Class</b> · <b>Label</b>	3 Flammable liquids 3+6.1
· <b>ADR, IMDG, IATA</b>	
	
· <b>Class</b> · <b>Label</b>	3 Flammable liquids 3+6.1
· <b>Packing group</b> · <b>DOT, ADR, IMDG, IATA</b>	II
· <b>Environmental hazards:</b> · <b>Marine pollutant:</b>	No
· <b>Special precautions for user</b> · <b>EMS Number:</b>	Warning: Flammable liquids F-E,S-D
· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	Not applicable.

(Contd. on page 9)





Trade name: 39650 (3965A & 3963B catalyzed)

(Contd. of page 8)

**· Transport/Additional information:**

**· DOT**

**· Quantity limitations**

On passenger aircraft/rail: 1 L

On cargo aircraft only: 60 L

**· ADR**

**· Excepted quantities (EQ)**

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

**· IMDG**

**· Limited quantities (LQ)**

1L

**· Excepted quantities (EQ)**

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

**· UN "Model Regulation":**

UN1992, Flammable liquids, toxic, n.o.s. (Acetone, HDI Prepolymer), 3 (6.1), II

**15 Regulatory information**

**· Safety, health and environmental regulations/legislation specific for the substance or mixture**

**· Sara**

**· Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

**· Section 313 (Specific toxic chemical listings):**

14807-96-6 Talc

ACRYLIC RESIN

1330-20-7 xylene

822-06-0 hexamethylene-di-isocyanate

**· TSCA (Toxic Substances Control Act):**

14807-96-6 Talc

28182-81-2 HDI Prepolymer

67-64-1 acetone

123-86-4 n-butyl acetate

110-43-0 heptan-2-one

763-69-9 ethyl 3-ethoxypropionate

1330-20-7 xylene

77-58-7 dibutyltin dilaurate

822-06-0 hexamethylene-di-isocyanate

**· Proposition 65**

**· Chemicals known to cause cancer:**

1330-20-7 xylene

**· Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

(Contd. on page 10)

Trade name: 39650 (3965A & 3963B catalyzed)

(Contd. of page 9)

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogeny categories**

· **EPA (Environmental Protection Agency)**

67-64-1	acetone	I
1330-20-7	xylene	I

· **TLV (Threshold Limit Value established by ACGIH)**

14807-96-6	Talc	A4
67-64-1	acetone	A4
1330-20-7	xylene	A4
77-58-7	dibutyltin dilaurate	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

HDI Prepolymer  
Talc  
POLYESTER RESIN  
heptan-2-one

· **Hazard statements**

H225 Highly flammable liquid and vapor.  
H302 Harmful if swallowed.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H317 May cause an allergic skin reaction.  
H351 Suspected of causing cancer.  
H371-H335 May cause damage to organs. May cause respiratory irritation.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P241 Use explosion-proof electrical/ventilating/lighting/equipment.  
P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P405 Store locked up.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 11)



Trade name: 39650 (3965A & 3963B catalyzed)

(Contd. of page 10)

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

· **Department issuing SDS:** Environment protection department.

· **Contact:** Steve Gaver

· **Date of preparation / last revision** 08/14/2014 / 1

· **Abbreviations and acronyms:**

*RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)*

*ICAO: International Civil Aviation Organization*

*ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)*

*IMDG: International Maritime Code for Dangerous Goods*

*DOT: US Department of Transportation*

*IATA: International Air Transport Association*

*ACGIH: American Conference of Governmental Industrial Hygienists*

*EINECS: European Inventory of Existing Commercial Chemical Substances*

*ELINCS: European List of Notified Chemical Substances*

*CAS: Chemical Abstracts Service (division of the American Chemical Society)*

*NFPA: National Fire Protection Association (USA)*

*HMIS: Hazardous Materials Identification System (USA)*

*VOC: Volatile Organic Compounds (USA, EU)*

*LC50: Lethal concentration, 50 percent*

*LD50: Lethal dose, 50 percent*

*Flam. Liq. 2: Flammable liquids, Hazard Category 2*

*Acute Tox. 4: Acute toxicity, Hazard Category 4*

*Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2*

*Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A*

*Resp. Sens. 1: Sensitisation - Respirat., Hazard Category 1*

*Skin Sens. 1: Sensitisation - Skin, Hazard Category 1*

*Carc. 2: Carcinogenicity, Hazard Category 2*

*STOT SE 2: Specific target organ toxicity - Single exposure, Hazard Category 2*

· **\* Data compared to the previous version altered.**