Issuing date 01-May-2015

Revision Date 04-May-2015

Version 1

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING


<u>Product identifier</u> Product name Product number	ACRY SOLVENT 9783
<u>Product type</u> Synonyms	Extremely flammable aerosol None
Supplier's details	
Recommended Use Uses advised against	Solvent cleaner. For Professional and Industrial Use Only. Not for sale to the general public.
Manufacturer/Supplier:	Transtar Autobody Technologies 2040 Heiserman Drive Brighton, MI 48116 810-360-1600
Emergency telephone number Chemical Emergency Phone Number	CHEMTREC: +001-703-527-3887 (INTERNATIONAL) 1-800-424-9300 (NORTH AMERICA)

2. HAZARDS IDENTIFICATION

Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Carcinogenicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 1
Flammable aerosols	Category 1
Gases under pressure	Compressed Gas

GHS Label elements, including precautionary statements



Precautionary Statements - Prevention

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Wear protective gloves/protective clothing/eye protection/face protection Wash face, hands and any exposed skin thoroughly after handling Avoid breathing dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area Keep away from heat/sparks/open flames/hot surfaces. — No smoking Do not spray on an open flame or other ignition source Pressurized container: Do not pierce or burn, even after use

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention Specific treatment (see first aid on this label) IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention Take off contaminated clothing and wash before reuse IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up Store in a well-ventilated place. Keep container tightly closed Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

None

Other information

· Toxic to aquatic life with long lasting effects

0% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %*
ALIPHATIC PETROLEUM DISTILLATE	64742-89-8	50-60
XYLENE	1330-20-7	10-20
PROPANE/ISOBUTANE/N-BUTANE	68476-86-8	10-20
ETHYL BENZENE	100-41-4	1-10

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

First aid measures for different exposure routes

Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.		
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.		
Inhalation	Move to fresh air. If breathing is difficult, give oxygen. Artificial respiration and/or oxygen may be necessary. If breathing has stopped, contact emergency medical services immediately.		
Ingestion	Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or Poison Control Center immediately.		
Most important symptoms/effects,	acute and delayed		
Main Symptoms	Causes skin irritation. Causes eye irritation. May cause respiratory irritation.May be harmful if swallowed.		
Indication of immediate medical attention and special treatment needed, if necessary			
Notes to physician	Treat symptomatically.		
5. FIRE-FIGHTING MEASURES			

Suitable Extinguishing Media

Water fog.Dry chemical. Carbon dioxide (CO2). Cool containers/tanks with water spray.

Unsuitable Extinguishing Media Keep away from sources of ignition - No smoking. Cool containers / tanks with water spray.

Specific hazards arising from the chemical

No information available.

Explosion Data

Sensitivity to Mechanical Impact none. Sensitivity to Static Discharge none.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions	Avoid contact with eyes. Avoid breathing vapors or mists. Contents under pressure. Do not puncture or incinerate cans.Do no stick pin or any other sharp object into opening on top of can. Avoid skin contact. Use with adequate ventilation. Keep container away from heat,flames, and all other sources of ignition. Keep can away from all sources of electricity such as electric motors and batteries. Do not spray on hot surfaces.	
Environmental precautions		
Environmental precautions	Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained.	
Methods and materials for contain	ment and cleaning up	
Methods for Containment	Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Prevent further leakage or spillage if safe to do so.	
Methods for cleaning up	Pick up and transfer to properly labeled containers. Soak up with inert absorbent material. Clean contaminated surface thoroughly. After cleaning, flush away traces with water. Take precautionary measures against static discharges.	
	7. HANDLING AND STORAGE	
Precautions for safe handling		
Advice on safe handling	Avoid contact with skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges.	
Conditions for safe storage, includ	ing any incompatibilities	
Technical measures/Storage conditions	Keep container tightly closed in a dry and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Keep in properly labeled containers. Keep out of the reach of children. Store locked up.	
	·	
Incompatible products	Strong acids, alkalis, or oxidizing agents.	

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
XYLENE 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m ³	-
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	74-98-6: TWA: 1000 ppm 106-97-8: STEL: 1000 ppm 75-28-5: STEL: 1000 ppm	74-98-6:TWA: 1000 ppm TWA: 1800 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m ³ 106-97-8: (vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m ³	74-98-6:IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m ³ 106-97-8:TWA: 800 ppm TWA: 1900 mg/m ³ 75-28-5:TWA: 800 ppm TWA: 1900 mg/m ³
ETHYL BENZENE 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m ³	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³

ACGIH: (American Conference of Governmental Industrial Hygienists) OSHA: (Occupational Safety & Health Administration) NIOSH IDLH: Immediately Dangerous to Life or Health

Other Exposure Guidelines	Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).
Exposure controls	
Engineering Measures	Showers Eyewash stations Ventilation systems.
Individual protection measures, su	ch as personal protective equipment
Eye/Face Protection	Safety glasses with side-shields.
Skin and body protection	Chemical resistant apron. Protective gloves.
Respiratory protection	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.
Hygiene measures	Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and chemical properties

Physical state Appearance Color	Aerosol Clear clear	Odor Odor Threshold	Solvent No information available
<u>Property</u> pH Melting/freezing point Boiling point/boiling range Flash Point	<u>Values</u> No information available No information available No information available -96.4 °C / -141 °F	Remarks • Methods	

Evaporation rate	No information available
Flammability (solid, gas)	No information available
Flammability Limits in Air	
upper flammability limit	No information available
lower flammability limit	No information available
Vapor pressure	No information available
Vapor density	No information available
Specific Gravity	0.720
Water solubility	Practically insoluble
Partition coefficient: n-octanol/wate	rNo information available
Autoignition temperature	No information available
Decomposition temperature	No information available
Viscosity	No information available
Explosive properties	No information available
Other information	

VOC Content(%)

100

10. STABILITY AND REACTIVITY

Reactivity_

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to Avoid

Extremes of temperature and direct sunlight.

Incompatible Materials

Strong acids, alkalis, or oxidizing agents.

Hazardous Decomposition Products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation	Vapors may irritate throat and respiratory system. May cause drownsiness and dizziness based on components. May cause irritation of respiratory tract. Avoid breathing vapors or mists.
Eye contact	Irritating to eyes. Avoid contact with eyes.
Skin contact	Irritating to skin. Repeated exposure may cause skin dryness or cracking. Prolonged skin contact may defat the skin and produce dermatitis. Avoid contact with skin.
Ingestion	May be harmful if swallowed. Aspiration into the lungs during swallowing may cause serious lung damage which may be fatal.

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
ALIPHATIC PETROLEUM DISTILLATE 64742-89-8	-	= 3000 mg/kg (Rabbit)	-

XYLENE	= 3500 mg/kg	(Rat)	> 4350 n	ng/kg (Rabbit)	= 29.08 mg/L (Rat)4 h	
1330-20-7		· · ·		3 3 4		
ETHYL BENZENE 100-41-4	-	- = 15400 mg/kg			-	
nformation on toxicologi	cal effects					
Symptoms	No informatic	on available.				
Delayed and immediate ef	fects as well as chronic	effects from	short and I	ong-term exposure	<u>)</u>	
Sensitization Germ Cell Mutagenicity Carcinogenicity	No informatic No informatic The table bel carcinogen.	on available.	vhether each	agency has evalua	ted a listed ingredient as a	
Chemical Name	ACGIH	IAR	С	NTP	OSHA	
XYLENE 1330-20-7	-	Grou	р 3	-	-	
ETHYL BENZENE 100-41-4	A3	Group 2B		-	-	
A3 - Animal Carcinogen IARC: (International Age Group 2B - Possibly Carci	erence of Governmental In ncy for Research on Cance nogenic to Humans as to Carcinogenicity in Hun	er)	nists)			
Reproductive toxicity	No informatio					
Specific target organ syst toxicity (single exposure)		No information available.				
Specific target organ syst toxicity (repeated exposu	emic No information	No information available.				
Target Organ Effects Aspiration hazard	Central nervo	Central nervous system, Eyes, Respiratory system, Skin. No information available.				
Numerical measures of to	xicity - Product Inform	ation				
Unknown Acute Toxicity	0% of the mix		•	(s) of unknown toxic	ity	

Unknown Acute Toxicity	
The following values are calculated	based on chapter 3.1 of the GHS document
ATEmix (oral)	17560 mg/kg
ATEmix (dermal)	5519 mg/kg
ATEmix (inhalation-dust/mist)	6 mg/l
	-

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia and other aquatic invertebrates
ALIPHATIC PETROLEUM	4700 mg/L EC50	-	-	-
DISTILLATE	Pseudokirchneriella			
64742-89-8	subcapitata 72h			

XYLENE	-	13.1 - 16.5 mg/L LC50	-	0.6 mg/L LC50 Gammarus
1330-20-7		Lepomis macrochirus 96h		lacustris 48h 3.82 mg/L
		flow-through 13.5 - 17.3		EC50 water flea 48h
		mg/L LC50 Oncorhynchus		
		mykiss 96h 2.661 - 4.093		
		mg/L LC50 Oncorhynchus		
		mykiss 96h static 23.53 -		
		29.97 mg/L LC50		
		Pimephales promelas 96h		
		static 30.26 - 40.75 mg/L		
		LC50 Poecilia reticulata 96h		
		static 7.711 - 9.591 mg/L		
		LC50 Lepomis macrochirus		
		96h static 13.4 mg/L LC50		
		Pimephales promelas 96h		
		flow-through 19 mg/L LC50		
		Lepomis macrochirus 96h		
		780 mg/L LC50 Cyprinus		
		carpio 96h semi-static 780		
		mg/L LC50 Cyprinus carpio		
		96h		
PROPANE/ISOBUTANE/N-	-	-	-	-
BUTANE				
68476-86-8				
ETHYL BENZENE	4.6 mg/L EC50	11.0 - 18.0 mg/L LC50	-	1.8 - 2.4 mg/L EC50
100-41-4	Pseudokirchneriella	Oncorhynchus mykiss 96h		Daphnia magna 48h
	subcapitata 72h 438 mg/L	static 7.55 - 11 mg/L LC50		
	EC50 Pseudokirchneriella	Pimephales promelas 96h		
	subcapitata 96h 2.6 - 11.3	flow-through 9.1 - 15.6 mg/L		
	mg/L EC50	LC50 Pimephales promelas		
	Pseudokirchneriella	96h static 32 mg/L LC50		
	subcapitata 72h static 1.7 -	Lepomis macrochirus 96h		
	7.6 mg/L EC50	static 4.2 mg/L LC50		
	Pseudokirchneriella	Oncorhynchus mykiss 96h		
	subcapitata 96h static	semi-static 9.6 mg/L LC50		
		Poecilia reticulata 96h static		

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical Name	log Pow
XYLENE 1330-20-7	3.15
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	2.8
ETHYL BENZENE 100-41-4	3.118

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment

Waste Disposal Methods This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261). Do not re-use empty containers.

Contaminated packaging

14. TRANSPORT INFORMATION

DOT Ground

CONSUMER COMMODITY ORM-D or LIMITED QUANTITY

ΙΑΤΑ	UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD. QTY.
IMDG	UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD. QTY.

15. REGULATORY INFORMATION

International Inventories

Chemical Name	TSCA	DSL/NDSL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
ALIPHATIC PETROLEUM DISTILLATE	Х	Х	Х	Not listed	Х	Х	Х	Х
XYLENE	Х	Х	Х	Х	Х	Х	Х	Х
PROPANE/ISOBUTA NE/N-BUTANE	Х	Х	Х	Not listed	Х	Х	Х	Х
ETHYL BENZENE	Х	Х	Х	Х	Х	Х	Х	Х

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

CHINA - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %*	SARA 313 - Threshold Values %
XYLENE - 1330-20-7	1330-20-7	10-20	1.0
ETHYL BENZENE - 100-41-4	100-41-4	1-10	0.1
SARA 311/312 Hazard Categories			
Acute Health Hazard	Yes		
Chronic Health Hazard	Yes		
Fire Hazard	Yes		
Sudden Release of Pressure Hazard	Yes		
Reactive Hazard	no		

Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
---------------	--------------------------------	------------------------	---------------------------	-------------------------------

9783	3
------	---

XYLENE 1330-20-7	100 lb			Х
ETHYL BENZENE 100-41-4	1000 lb	Х	Х	Х

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
XYLENE 1330-20-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
ETHYL BENZENE 100-41-4	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

U.S. State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical Name	California Prop. 65
ETHYL BENZENE - 100-41-4	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
XYLENE	X	X	Х
1330-20-7			
ETHYL BENZENE	X	X	Х
100-41-4			

EPA Pesticide Registration Number Not applicable

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

16. OTHER INFORMATION

<u>NFPA</u>	Health Hazard 2	Flammability 4	Instability 0	Physical and chemical hazards
HMIS	Health Hazard 2	Flammability 4	Physical Hazard 1	Personal protection B

Prepared By

Transtar Autobody Technologies

Issuing date01-May-2015Revision Date04-May-2015Revision Note04-May-2015No information available04-May-2015

Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet